

Declaration of Performance (DoP)

N° 0200002000/01

In accordance with annex III of the EU regulation 305/2011

1. Unique identification code of the product-type:

DETAFLEX 1500

2. Type, batch or serial number, or any other element allowing identification of the construction product as required pursuant to Article 11 (4):

Batch number: See entry on packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Sealant for facade application exterior and interior – Conform EN 15651-1:2012 Type F EXT-INT

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**DL CHEMICALS
Roterijstraat 201-203
B 8793 Waregem**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2) :

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

The notified body **GINGER CEBTP**, identification number **NB 0074**, performed the determination of the product type based on type testing under system 3 and issued : a test report

8. In case of the declaration of performance concerning a construction product of which a European Technical Assessment has been issued :

Not applicable

Declaration of Performance (DoP)

N° 0200002000/01

In accordance with annex III of the EU regulation 305/2011

9. Declared Performances:

Essential characteristics	Performance	Technical harmonised specification
Reaction to fire (classification according EN 13501-1:2007)	NPD	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	EN 15651-1:2012
Water and air tightness		
Resistance to flow (according EN ISO 7390)	≤ 3mm	EN 15651-1:2012
Loss of volume (according EN ISO 10563)	≤ 10 %	EN 15651-1:2012
Tensile properties for "non structural" low modulus sealants used in joints in "cold climate" areas (-30°C) – according EN ISO 8339	NPD	EN 15651-1:2012
Tensile properties for "non structural" sealants used in joints in "cold climate" areas (-30°) at maintained extension – according EN ISO 8340	NPD	EN 15651-1:2012
Tensile properties • after immersion in water (according EN ISO 10591) • at maintained extension after water immersion (according EN ISO 10590)	Pass	EN 15651-1:2012
Durability	Pass	EN 15651-1:2012
Conditionning : methode A Substrate : • Façade : Anodized Aluminium + M2 Concrete		

10. The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9

This declaration of performance is issued under the sole responsibility of the manufacturer identified under point 4.

Signed for and on behalf of the manufacturer by



Ing. H Vranken
Technical Support Manager
Waregem – May 2014